CLAIMS

- 1. (previously presented) An Active Carbon Nanofiber-based battery comprising a cell trough filled with electrolyte with a cell cap, a spring coil locking onto said cell trough, an anode/cathode substrate plate installed within the cell trough linking with its respective separation membrane, and positive and negative terminals installed outside the cell cap connecting to said anode/cathode substrate plate respectively; whereas the anode substrate plate is composed of an aluminum plate and a Carbon Nanofiber layer spray-coated on the aluminum plate surface; whereas the cathode substrate plate is composed of a copper plate and a Carbon Nanofiber layer spray-coated on the copper plate surface, wherein gaps are formed between sets of substrate plates and their separation membranes, whereby the battery can have a large capacity with a capacitor-like functionality.
- 2. (original) The Active Carbon Nanofiber-based battery in claim 1, wherein the individual tube diameter of the Carbon Nanofiber layer is 20-80nm, with the length of 200-300nm.
- 3. (cancelled) The Active Carbon Nanofiber-based battery in claim 1, wherein each set of the substrate plate and its separation membrane has a gap in between, forming a capacitor-like functionality.
- 4. (original) The Active Carbon Nanofiber-based battery in claim 1, wherein the separation membrane is made by high-molecule, high-insulation cloth, with the size of the battery inner trough.
- 5. (previously presented) The Active Carbon Nanofiber-based battery in claim 1, wherein individual tube diameter of the Carbon Nanofiber layer is 20nm, with the length of 290nm.
- 6. (previously presented) The Active Carbon Nanofiber-based battery in claim 1, wherein individual tube diameter of the Carbon Nanofiber layer is 80nm, with the length of 300nm.
- 7. (previously presented) The Active Carbon Nanofiber-based battery in claim 1, wherein individual tube diameter of the Carbon Nanofiber layer is 60nm, with the length of 200nm.
- 8. (previously presented) The Active Carbon Nanofiber-based battery in claim 1, wherein capacitance ranges from 8 uf to 3000 uf.